




Airhandlers

LU05BE Airhandler

Low-noise water-cooled ventilation unit with a 50 kW cooling capacity, fitted with continuously variable ventilation control that can blow in three directions. The airhandler is equipped with an extra defrost element which makes it also suitable for low temperature applications. For electrical defrosting a 32 A CEE connection is required. The unit is equipped with a condensate pump, ready for connection and easy to install by using shortcuts. The unit is easy to move with a pallet cart or forklift.

Technical specifications LU05BE



| | | | | | |
|-------------------------------|------------------------|-------------------------------|---------------|-----------------------|----------|
| Cooling capacity ¹ | 50 kW | Power connection | 230/1/50 EURO | Length | 1620 mm |
| Current (nominal) | 7.5 A | Recommended Fuses | 16A A | Width | 780 mm |
| Capacity steps | Freq. contr. | Phases | 1 + N + PE | Height | 2250 mm |
| Max. air flow | 7500 m ³ /h | Power connection ² | 32A | Weight | 475 kg |
| Voltage | 230 V | Recommended Fuses | 32A A | Sound level (at 10 m) | 45 dB(A) |
| External (Air) pressure | 300 Pa | Phases | 3 + N + PE | | |

¹ Cooling: Water 6 - 12 °C, air 30 °C / 60% RV

² When using electric defrost.