



Freezer rooms

VC05 Freezer unit

Ready-for-use mobile freezer unit with a volume of 30 m³ and a large freezing overcapacity (temperature range down to minus 30 °C*). The frozen storage cell has been fitted with a flat anti-skid floor, lighting, a door with frame heating that opens smoothly (also from the inside), and has a very low entry height. The frozen storage cell meets the HACCP/GMP requirements and is easy to install, even in locations that are difficult to reach, as well indoors as outdoors. The storage cell is low noise and low power.

Technical specifications VC05



| | | | | | |
|--------------------------------------|-------------------|-------------------|------------|-----------------------|------------------------|
| Amount of pallets (euro) | 10 | Current (max) | 9.4 A | Height (internal) | 2260 mm |
| Volume | 30 m ³ | Recommended fuses | 16 A | Door height | 2100 mm |
| Min. inside temperature ¹ | -30 °C | Phases | 3 + N + PE | Door width | 1400 mm |
| Max. inside temperature | -15 °C | Length (external) | 6000 mm | Threshold height | 180 mm |
| Min. outside temperature | -20 °C | Width (external) | 2500 mm | Max. load | 1200 Kg/m ² |
| Power connection | 16 A CEE | Height (external) | 2500 mm | Weight | 1750 kg |
| Voltage | 400 V | Length (internal) | 5840 mm | Sound level (at 10 m) | 47 dB(A) |
| Current (nominal) | 5.3 A | Width (internal) | 2340 mm | | |

¹ After approval of Coolworld International